

<p style="text-align: center;"><b>Wideband Compact Cryogenic Receiver QRFH</b> <b>- SN: 01 -</b> <b>FAT</b></p>
---

## Test Report

**Document Reference** : REP/1704/3986

**Issue** : 0.2

**Date** : 06<sup>th</sup> December 2016

**Contract** : PRP/685/3606v1.0  
11.Apr.2016 + Letter  
UTAS 13.Apr.2016

	Name	Signature
<b>Prepared by</b> :	Callisto Team	
<b>Reviewed/Approved by</b> :	Steve RAWSON	

**Document Amendment Record**

Issue No.	Date	File Name	Details
0.1	30.11.16	3986 0.1	Draft
0.2	06.12.16	3986 0.2	Second draft after internal discussion. Addition of the gain extracted from NT measurement.

**Document Distribution Record**

Name	Organisation	Media	Number of Copies
Callisto Team	Callisto	PDF	1
Simon Ellingsen	UTAS	PDF	1

## TABLE OF CONTENTS

<b>Document Amendment Record .....</b>	<b>2</b>
<b>Document Distribution Record .....</b>	<b>2</b>
<b>TABLE OF CONTENTS .....</b>	<b>3</b>
<b>LIST OF FIGURES .....</b>	<b>4</b>
<b>LIST OF TABLES .....</b>	<b>4</b>
<b>1. INTRODUCTION .....</b>	<b>5</b>
1.1 PURPOSE.....	5
1.2 APPLICABLE & REFERENCE DOCUMENTS.....	5
1.2.1 <i>Applicable Documents</i> .....	5
<b>2. TEST RESULTS SUMMARY .....</b>	<b>6</b>
<b>3. DETAILED TESTS RESULTS.....</b>	<b>9</b>
3.1 THERMAL TESTS .....	9
3.2 RF TESTS .....	13
3.2.1 <i>Noise temperature measurement</i> .....	20
3.2.2 <i>Noise Calibration</i> .....	26
3.2.3 <i>Phase Calibration</i> .....	30
<b>LIST OF ABBREVIATIONS .....</b>	<b>37</b>

## LIST OF FIGURES

FIGURE 3-1 : COOLDOWN .....	11
FIGURE 3-2: STABILIZATION – BASE TEMPERATURE .....	11
FIGURE 3-3 : WARMUP .....	12
FIGURE 3-4: GAIN VIA TEST INPUT FOR TLNA=76K.....	15
FIGURE 3-5: OUTPUT RETURN LOSS .....	15
FIGURE 3-6: GAIN VIA TEST INPUT STABILITY OVER 60MIN (1 SAMPLE PER MIN) @2GHZ .....	16
FIGURE 3-7: GAIN VIA TEST INPUT STABILITY OVER 60MIN (1 SAMPLE PER MIN) @8GHZ .....	16
FIGURE 3-8: GAIN VIA TEST INPUT STABILITY OVER 60MIN (1 SAMPLE PER MIN) @14GHZ.....	17
FIGURE 3-9: GAIN VIA TEST INPUT STABILITY OVER 60SEC (1 SAMPLE PER SEC) @2GHZ.....	17
FIGURE 3-10: GAIN VIA TEST INPUT STABILITY OVER 60SEC (1 SAMPLE PER SEC) @8GHZ.....	18
FIGURE 3-11: GAIN VIA TEST INPUT STABILITY OVER 60SEC (1 SAMPLE PER SEC) @14GHZ.....	18
FIGURE 3-12: GAIN EXTRACTED FROM NT MEASUREMENT. ....	19
FIGURE 3-13: RFI SURVEY IN THE CALLISTO LABORATORY, OUTPUT OF AN AMPLIFIER, AT LOW FREQUENCY THE RFI ARE MIXED BY THE AMPLIFIER. ....	20
FIGURE 3-14: RFI SURVEY OF THE NT MEASUREMENT PLACE.....	21
FIGURE 3-15: NT MEASUREMENT TEST SET-UP. ....	22
FIGURE 3-16: NT MEASUREMENT RAW DATA FOR TLNA=71K.....	23
FIGURE 3-17: NT MEASUREMENT CLEANED DATA FOR TLNA=71K .....	24
FIGURE 3-18: NT MEASUREMENT CLEANED DATA TREND FOR TLNA=71K.....	25
FIGURE 3-19: NOISE CALIBRATION CIRCUIT .....	26
FIGURE 3-20: Y-FACTOR MEASURED WITH THE NOISE DIODE ON (TN=10K) AND OFF @4GHZ PORT X28	
FIGURE 3-21: Y-FACTOR MEASURED WITH THE NOISE DIODE ON (TN=10K) AND OFF @4GHZ PORT Y28	
FIGURE 3-22: Y-FACTOR MEASURED WITH THE NOISE DIODE ON (TN=10K) AND OFF @9GHZ PORT X29	
FIGURE 3-23: Y-FACTOR MEASURED WITH THE NOISE DIODE ON (TN=10K) AND OFF @9GHZ PORT Y29	
FIGURE 3-24: NOISE CALIBRATION CIRCUIT .....	30
FIGURE 3-25: COMB GENERATOR OUTPUT WITH +10DBM 10MHZ INPUT @2GHZ .....	30
FIGURE 3-26: COMB GENERATOR OUTPUT WITH +10DBM 10MHZ INPUT @4GHZ .....	31
FIGURE 3-27: COMB GENERATOR OUTPUT WITH +10DBM 10MHZ INPUT @6GHZ .....	31
FIGURE 3-28: COMB GENERATOR OUTPUT WITH +10DBM 10MHZ INPUT @8GHZ .....	32
FIGURE 3-29: COMB GENERATOR OUTPUT WITH +10DBM 10MHZ INPUT @10GHZ .....	33
FIGURE 3-30: COMB GENERATOR OUTPUT WITH +10DBM 10MHZ INPUT @12GHZ .....	33
FIGURE 3-31: COMB GENERATOR OUTPUT WITH +10DBM 10MHZ INPUT @14GHZ .....	34
FIGURE 3-32: PORT X OUTPUT @14GHZ WHEN COMB GENERATOR ON WITH +10DBM INPUT POWER	35
FIGURE 3-33: PORT Y OUTPUT @14GHZ WHEN COMB GENERATOR ON WITH +10DBM INPUT POWER	36

## LIST OF TABLES

TABLE 2-1: TEST RESULTS SUMMARY .....	8
TABLE 3-1: TEST RESULT SHEET N°1 - THERMAL TESTS .....	10
TABLE 3-2: TEST RESULT SHEET N°2 – RF TESTS .....	14

## 1. INTRODUCTION

### 1.1 Purpose

Tests have been conducted on the Wideband Compact Cryogenic Receiver QRFH SN01 in Callisto laboratory and outside for the noise temperature according to the procedures described in test plan AD 3.

The tests included RF testing and cryogenic testing.

### 1.2 Applicable & Reference Documents

This section lists other documents which are referred to in the main body of this document. In cases when the document cited is listed without an issue number, revision number or date, then the reader should refer to the latest available issue.

#### 1.2.1 Applicable Documents

- AD 1 Callisto Proposal , Ref. PRP/685/3606 issue 1.0 dated 11<sup>th</sup> April 2016
- AD 2 User Manual, QRFH Compact Wideband Cryogenic Receiver, DOC/1704/3991
- AD 3 Test Plan Procedure QRFH Compact Receiver, TST/1704/3990, Issue 1.0
- AD 4 Interface Control Document, ICD/1704/3992, issue 1.0

## 2. TEST RESULTS SUMMARY

Result "R" column = Passed (P), Marginal (M), Failed (F)

Parameter	Specifications	Results	Verification Method	R	Comments
<b>Frequency Band</b>	2 – 14 GHz		AT		
<i>Port X</i>		2-14GHz		P	
<i>Port Y</i>		2-14GHz		P	
<b>Noise Temperature</b>	<40K		AT		at cryogenic temperature
<i>Port X</i>		97% of the meas <40K		P	TLNA=71K
<i>Port Y</i>		94% of the meas <40K		P	TLNA=71K
<b>Gain</b>	>55dB		AT		
<i>Port X</i>		55.2dBmin		P	Gain extracted from NT meas
<i>Port Y</i>		55.4dBmin		P	
<b>Gain Flatness</b>	10dBpp		AT		
<i>Port X</i>		7.8dBpp		P	Worst case, gain extracted from NT meas
<i>Port Y</i>		8.7dBpp		P	
<b>Output Return Loss</b>	10dBmin		AT		
<i>Port X</i>		11.8dBmin		P	14dB typical
<i>Port Y</i>		11.8dBmin		P	14dB typical

<b>Pout 1dB</b>	+20dBm		CT; D		
<i>Port X</i>		+20dBm		P	
<i>Port Y</i>		+20dBm		P	
<b>Gain via test input</b>			AT		No specification defined for this parameter
<i>Port X</i>		18.7dB<G<43.5dB			
<i>Port Y</i>		19.7dB<G<43.8 dB			
<b>Cooldown Time to reach NT&lt;40K</b>	<5 hours		AT		
<i>Port X</i>		4Hrs		P	
<i>Port Y</i>		4Hrs		P	
<b>Noise calibration</b>	None		AT	P	The NT measurement performed with the noise diode is comparable with the NT measurement done with the sky method
<b>Phase calibration</b>	None		AT	P	The minimum picket level at 14GHz available at the output of the receiver is around -70.5dBm.
<b>Cold Head Base Temperature</b>	80K	75K	AT	P	
<b>Cooldown Time to base temperature</b>	not specified	1h16	AT		
<b>Warm-up Time (base temp--&gt;280K)</b>	not specified	15Hrs	AT		
<b>RF Input</b>	Free space radiation	Ok	D	P	
<b>RF output connector</b>	SMA	Ok	I	P	
<i>Port X</i>		Ok		P	
<i>Port Y</i>		Ok		P	

<b>10MHz Phase Calibration Input</b>	SMA	Ok	I	P	
<b>Dimensions (mm)</b>	l=612 * Phi=311		I	P	Excluding supports and connectors
<b>Weight (kg)</b>	<27kg	26.8Kg	AT	P	Excluding supports and cables
<b>Operating Orientation</b>	Any		D	P	
<b>Operating Temperature</b>	-10°C to +40°C		D	P	
<b>Storage Temperature</b>	-40°C to +60°C		D	P	
<b>Relative Humidity</b>	to 90% non condensing		D	P	
<b>Ventilation Requirement</b>	Forced air cooling	Ok	I	P	
<b>Max Power Consumption</b>	400W	345W	AT	P	
<b>Input Voltage</b>	90—264VAC / 47—63Hz	Ok	D	P	
<b>Distance between receiver and PSU Drawer</b>	<20m	Ok	AT	P	Split M&C – 5m between receiver and DAQ-PSU enclosure – 20mbetween DAQ-PSU enclosure and PC enclosure
<b>LMS parameters display</b>		Ok	AT	P	
<b>LMS functions</b>		Ok	AT	P	
<b>LMS log files</b>		Ok	AT	P	
<b>Remote communication</b>		Ok	AT	P	
<b>Cryocooler MTTF</b>	200,000 hours		D	P	

**Table 2-1: Test Results Summary**



### 3. DETAILED TESTS RESULTS


#### 3.1 Thermal Tests

Result "R" column = Passed (P), Marginal (M), Failed (F)


Ref	Parameter / Requirement	Spec	Result	R	Comments
	Date: 02/07/15				
	<b>Cooldown time</b>	---			
	<b>to RF specification</b>	5 hours	see Table 2-1		5 hours expected to reach RF specification (NT<40K)
	<b>on cold head</b>	295K to <100K	0h21	-	
	“”	295K to Base temperature	1h16	-	
	<b>on LNA</b>	295K to <100K	0h27	-	
	“”	295K to Base temperature	7hrs	-	
	<b>on feed base plate</b>	295K to <150K	4h46	-	
	“”	295K to Base temperature	15hrs	-	
	<b>Base Temperatures</b>	<b>Tset = 75K</b>			
	<b>Cold head</b>	~75K±0.5K	75K	P	
	<b>LNA</b>	<85K	76K	P	
	<b>Feed [base]</b>	<130K	123K	P	
	<b>Feed [top]</b>	<150K	135K	P	
	<b>Cooler Input Power</b>		60W		
	<b>Compressor Temperature</b>	<70°C	20°C	P	

Ref	Parameter / Requirement	Spec	Result	R	Comments
	<b>Ambient(Room) Temperature</b>		15°C		Receiver in Callisto Garage, winter time.
	<b>Warmup time (no heaters)</b>	100K to 295K No spec.	15hrs		


**Table 3-1: Test Result Sheet n°1 - Thermal Tests**



**Figure 3-1 : Cooldown**



**Figure 3-2: Stabilization – Base Temperature**



**Figure 3-3 : Warmup**

### 3.2 RF Tests

Result "R" column = Passed (P), Marginal (M), Failed (F)

Ref	Parameter / Requirement	Spec	Result		R	Comments	
	<b>Cryogenic Temperature</b>	---				<b>TcryoLNA = 76K</b>	
	<b>Frequency Band</b>	2 – 14 GHz	2-14GHz				
	<b>Noise Temperature</b>	Max<40K		Port X	Port Y	P	<p>Due to winter condition, the physical temperatures of the system were lower than set (75K) and so the NT measured is lower than predicted (TLNA=71K; Tbase feed=111K and Ttopfeed=124K).  On the other hand the NT measurement is degraded by the RFI observed at low frequency. (See NT graph Figure 3-16: NT Measurement raw data for TLNA=71K Figure 3-16)</p> <p>Port X: 97% of the NT measurement is in specification from 3GHz up to 14GHz.  Port Y: 94% of the NT measurement is in specification from 3GHz up to 14GHz.</p>
			Min Meas	22.5K	23.7		
			Max Meas	42.1K	50.3K		
			Mean Meas	30.2K	30.5K		
			Min Trend	27K	26.5K		
			Max trend	40K	43K		
	<b>Gain</b>	>55dB	Port X	Port Y	P	Gain extracted from NT meas	
			55.2dBmin	55.4dBmin			
	<b>Gain Flatness</b>	10dBpp	7.8dBpp	8.7dBpp	P	Worst case gain extracted from NT meas	
	<b>Output Return Loss</b>	>10dB	11.8dB min	11.8dB min	P	14dB typical	
	<b>Pout 1dB</b>	+20dBm	+20dBm		P	By design	
	<b>Gain via test input (Port X)</b>	-	18.7dB<Gain<43.5dB				

Ref	Parameter / Requirement	Spec	Result	R	Comments
	<b>Gain via test input (Port Y)</b>	-	19.7dB<Gain<43.8 dB		
	<b>Gain via test input stability (Port X)</b>	-	@2GHz / 60min: 0.04dBpp @8GHz / 60min: 0.03dBpp @14GHz / 60min: 0.07dBpp @2GHz / 60sec: 0.02dBpp @8GHz / 60sec: 0.01dBpp @14GHz / 60sec: 0.03dBpp		Most of the gain variation is probably due to the measurement set-up. A specific calibration of the VNA as to be performed at 14GHz to improve the test set-up stability.
	<b>Gain via test input stability (Port Y)</b>	-	@2GHz / 60min: 0.03dBpp @8GHz / 60min: 0.05dBpp @14GHz / 60min: 0.05dBpp @2GHz / 60sec: 0.02dBpp @8GHz / 60sec: 0.03dBpp @14GHz / 60sec: 0.14dBpp		Most of the gain variation is probably due to the measurement set-up. A specific calibration of the VNA as to be performed at 14GHz to improve the test set-up stability.

**Table 3-2: Test Result Sheet n°2 – RF Tests**




Figure 3-4: Gain via test input for TLNA=76K






Figure 3-5: Output Return Loss




**Figure 3-6: Gain via test input stability over 60min (1 sample per min) @2GHz**




**Figure 3-7: Gain via test input stability over 60min (1 sample per min) @8GHz**







**Figure 3-8: Gain via test input stability over 60min (1 sample per min) @14GHz**



**Figure 3-9: Gain via test input stability over 60sec (1 sample per sec) @2GHz**



**Figure 3-10: Gain via test input stability over 60sec (1 sample per sec) @8GHz**




**Figure 3-11: Gain via test input stability over 60sec (1 sample per sec) @14GHz**

The gain of the receiver has been extracted from the noise temperature measurement using the following formula:

$$G = \frac{P_{hot}}{(T_e - T_{hot}) \times B \times k}$$

With:

- G = Gain of the receiver
- Phot = Power measure at the output of the receiver when the hot load is in front of the receiver
- Te = Noise temperature of the receiver
- Thot = Noise temperature of the hot load
- B = Bandwidth (Resolution Band Width set on the spectrum analyser)
- K = Boltzmann constant




**Figure 3-12: Gain extracted from NT measurement.**

The gain extracted from the NT measurement is noisy but it gives a good trend for the overall gain of the receiver.

### 3.2.1 Noise temperature measurement

Due to the increase of mobile phone antenna installation around the Callisto premises it become more and more difficult to make clean and valuable noise temperature measurement on the QRFH receiver. Indeed the increase of RFI measured in the Callisto laboratory is problematic for this type of measurement:




Date: 22.NOV.2016 17:08:54

**Figure 3-13: RFI survey in the Callisto laboratory, output of an amplifier, at low frequency the RFI are mixed by the amplifier.**

The RFI have a direct impact on the NT measurement (noise peak) but the RFI are also mixed by the amplifiers of the receiver and so the overall noise floor increases.

It is difficult for us to find a convenient place without RFI to make the NT measurement but we have tried to move to a place with less RFI (countryside):




Date: 28.NOV.2016 14:04:31


Figure 3-14: RFI survey of the NT measurement place.



**Figure 3-15: NT measurement test set-up.**



**Figure 3-16: NT Measurement raw data for TLNA=71K**



**Figure 3-17: NT Measurement cleaned data for TLNA=71K**







Figure 3-18: NT Measurement cleaned data trend for TLNA=71K

### 3.2.2 Noise Calibration

The purpose of this circuit is to inject two levels of noise in the QRFH receiver in order to do a noise measurement using the Y-factor method. The noise is generated by a noise diode and the level of noise is set using a variable attenuator. This noise signal is injected inside the QRFH feed by a probe antenna.



**Figure 3-19: Noise calibration circuit**

The two levels of noise have been defined by UTAS  $Tn1=10K$  and  $Tn2=0.5K$ . The theoretical attenuation ( $At$ ) required to achieve  $Tn1$  and  $Tn2$  has been calculated according to the ENR of the noise diode at  $50^{\circ}C$  from the calibration data given by the noise diode manufacturer. The following tables give the variable attenuator settings to generate  $Tn1$  and  $Tn2$ :

1704 QRFH SN01 Attenuator Settings for Noise Calibration Port X (ND AE849)										
Freq (GHz)	ND ENR (dB) @50°C	Td ND @50°C (K)	At1 calculated for Tn1=10K (dB)	Att1 set on HMC-C018 (dB)	At1 measured (dB)	Effective Tn1 (K)	At2 calculated for Tn2=0.5K (dB)	Att2 set on HMC-C018 (dB)	At2 measured (dB)	Effective Tn2 (K)
2	31.99	458851.93	46.62	10.0	46.60	10.04	59.63	23	59.5	0.51
3	31.70	429231.43	46.33	21.0	46.40	9.83	59.34	31.5	56.8	0.90
4	31.61	420433.84	46.24	14.0	46.00	10.56	59.25	27.5	59.4	0.48
5	31.51	410870.20	46.14	18.0	45.90	10.56	59.15	31	59.3	0.48
6	31.45	405236.82	46.08	14.5	45.90	10.42	59.09	27.5	59	0.51
7	31.28	389691.84	45.91	15.5	46.10	9.57	58.92	27.5	58.5	0.55
8	31.11	374743.59	45.74	13.0	45.70	10.09	58.75	25.5	58.5	0.53
9	31.21	383465.73	45.84	8.0	46.10	9.41	58.85	20.5	58.9	0.49
10	31.23	385234.39	45.86	7.5	45.90	9.90	58.87	20	59	0.48
11	31.26	387902.70	45.89	6.0	45.80	10.20	58.90	19	58.8	0.51
12	31.38	398762.17	46.01	4.0	45.80	10.49	59.02	17.5	59	0.50
13	31.56	415624.49	46.19	1.5	46.30	9.74	59.20	14.5	59.2	0.50
14	31.55	414669.25	46.18	0.0	47.00	8.27	59.19	12.5	59.3	0.49

1704 QRFH SN01 Attenuator Settings for Noise Calibration Port Y (ND AE849)										
Freq (GHz)	ND ENR (dB) @50°C	Td ND @50°C (K)	At1 calculated for Tn1=10K (dB)	Att1 set on HMC-C018 (dB)	At1 measured (dB)	Effective Tn1 (K)	At2 calculated for Tn2=0.5K (dB)	Att2 set on HMC-C018 (dB)	At2 measured (dB)	Effective Tn2 (K)
2	31.99	458851.93	46.62	10.0	46.60	10.04	59.63	23	59.5	0.51
3	31.70	429231.43	46.33	21.0	46.40	9.83	59.34	31.5	56.8	0.90
4	31.61	420433.84	46.24	14.0	46.00	10.56	59.25	27.5	59.4	0.48
5	31.51	410870.20	46.14	18.0	45.90	10.56	59.15	31	59.3	0.48
6	31.45	405236.82	46.08	14.5	45.90	10.42	59.09	27.5	59	0.51
7	31.28	389691.84	45.91	15.5	46.10	9.57	58.92	27.5	58.5	0.55
8	31.11	374743.59	45.74	13.0	45.70	10.09	58.75	25.5	58.5	0.53
9	31.21	383465.73	45.84	8.0	46.10	9.41	58.85	20.5	58.9	0.49
10	31.23	385234.39	45.86	7.5	45.90	9.90	58.87	20	59	0.48
11	31.26	387902.70	45.89	6.0	45.80	10.20	58.90	19	58.8	0.51
12	31.38	398762.17	46.01	4.0	45.80	10.49	59.02	17.5	59	0.50
13	31.56	415624.49	46.19	1.5	46.30	9.74	59.20	14.5	59.2	0.50
14	31.55	414669.25	46.18	0.0	47.00	8.27	59.19	12.5	59.3	0.49

Find below a description of each column of the table above:

- ND ENR @50°C (dB): ENR of the noise diode @50°C from the calibration data given by the noise diode manufacturer.
- Td ND @50°C (K): Noise generated by the noise diode in Kelvin. Derivate from the noise diode ENR @50°C.
- At1 calculated for Tn1=10K (dB): Attenuation At1 calculated in order to inject Tn1=10K in the QRFH receiver.
- Att1 set on HMC-C018 (dB): Attenuation set on the variable attenuator to achieve the closest value of AT1 calculated in order to inject Tn1. The variable attenuator has a minimum resolution of 0.5dB.
- At1 measured (dB): Due to the resolution of the variable attenuator it is not possible to achieve the exact calculated value of At1. At1 measured is the closest value achievable.
- Effective Tn1 (K): According to the At1 measured the effective Tn1 has been re-calculated.

The last 4 columns are identical to the previous ones but for the Tn2=0.5K.


The operating of the noise calibration has been tested. The Y-factor of the receiver has been measured when the noise diode is off and when the noise calibration circuit injects Tn=10K. The measurement has been performed at 4GHz and 9GHz on both port. The receiver noise temperature has been calculated using the Noise Adding Radiometer formula:

$$NT(K) = \frac{Tn}{(Y - 1)}$$

	Output Power ND Off (dBm)	Output Power ND On (Tn=10K) (dBm)	Y-factor (dB)	Y-factor (ratio)	NT (K) ND method
Port X @4GHz	-49.5	-48.53	0.97	1.25025903	40.0
Port Y @4GHz	-49.1	-48.08	1.02	1.264736347	37.8
Port X @9GHz	-53.89	-53.02	0.87	1.22179966	45.1
Port Y @9GHz	-53.96	-53.11	0.85	1.216186001	46.3


The receiver noise temperatures in the table above are not corrected (Tsky...) and are in the order of magnitude of the measurements performed with the hot/cold method using the sky as a cold load.

The noise calibration circuit is operational.




Date: 1.DEC.2016 15:36:33

**Figure 3-20: Y-factor measured with the noise diode On ( $T_n=10K$ ) and off @4GHz port X**




Date: 1.DEC.2016 15:34:39

**Figure 3-21: Y-factor measured with the noise diode On ( $T_n=10K$ ) and off @4GHz port Y**



Date: 1.DEC.2016 15:45:31

Figure 3-22: Y-factor measured with the noise diode On ( $T_n=10K$ ) and off @9GHz port X




Date: 1.DEC.2016 15:43:55

Figure 3-23: Y-factor measured with the noise diode On ( $T_n=10K$ ) and off @9GHz port Y


### 3.2.3 Phase Calibration

The purpose of the phase calibration circuit is to generate a comb spectrum signal up to 14GHz with spectral lines at 10MHz spacing, which are derived from an input reference frequency signal available in the station. The phase calibration circuit configuration is shown below:




**Figure 3-24: Noise calibration circuit**

The comb generator has been tested along with +10dBm input power and 15V/70mA power supply:




Date: 5.DEC.2016 12:28:40

**Figure 3-25: Comb generator output with +10dBm 10MHz input @2GHz**




Date: 5.DEC.2016 12:29:45

Figure 3-26: Comb generator output with +10dBm 10MHz input @4GHz



Date: 5.DEC.2016 12:30:36


Figure 3-27: Comb generator output with +10dBm 10MHz input @6GHz



Date: 5.DEC.2016 12:31:15


**Figure 3-28: Comb generator output with +10dBm 10MHz input @8GHz**






Date: 5.DEC.2016 12:33:02

**Figure 3-29: Comb generator output with +10dBm 10MHz input @10GHz**



Date: 5.DEC.2016 12:39:20

**Figure 3-30: Comb generator output with +10dBm 10MHz input @12GHz**




Date: 5.DEC.2016 12:40:53

**Figure 3-31: Comb generator output with +10dBm 10MHz input @14GHz**


The minimum output level of the picket is higher than -80dBm up to 14GHz with +10dBm input power.

In order to validate the phase calibration signal injection, the output of the receiver has been measured with the comb generator on (+10dBm input power) and with the variable attenuator set to the minimum attenuation. The measurement has been done at 14GHz where the amplitude of the picket are the lowest:



Date: 29.NOV.2016 19:03:39

**Figure 3-32: Port X output @14GHz when comb generator on with +10dBm input power**



Date: 29.NOV.2016 19:07:12

**Figure 3-33: Port Y output @14GHz when comb generator on with +10dBm input power**

The maximum picket level at 14GHz available at the output of the receiver is around -71.5dBm.

The phase calibration circuit is operational.

## LIST OF ABBREVIATIONS

<b>Acronym</b>	<b>Meaning</b>
<b>A</b>	<b>Ampere</b>
<b>AD</b>	<b>Applicable Document</b>
<b>AIL</b>	<b>Action Item List</b>
<b>DC</b>	<b>Direct Current</b>
<b>DR</b>	<b>Design Review</b>
<b>FAT</b>	<b>Factory Acceptance Tests</b>
<b>h</b>	<b>Hour</b>
<b>ICD</b>	<b>Interface Control Document</b>
<b>IR</b>	<b>Infra-Red</b>
<b>IRF</b>	<b>Infra-Red Filter</b>
<b>K</b>	<b>Kelvin</b>
<b>LAN</b>	<b>Local Area Network</b>
<b>LNA</b>	<b>Low Noise Amplifier</b>
<b>mA</b>	<b>MilliAmpere</b>
<b>mbar</b>	<b>Millibar</b>
<b>min</b>	<b>Minute</b>
<b>MTBF</b>	<b>Mean Time Between Failure</b>
<b>mV</b>	<b>MilliVolt</b>
<b>NT</b>	<b>Noise Temperature</b>
<b>OSAT</b>	<b>On-Site Acceptance Tests</b>
<b>PC</b>	<b>Personal Computer</b>
<b>pre-FAT</b>	<b>preliminary Factory Acceptance Tests</b>
<b>s</b>	<b>Second</b>
<b>sec.</b>	<b>Second</b>
<b>SoW</b>	<b>Statement of Work</b>
<b>TBC</b>	<b>To Be Confirmed</b>
<b>TBD</b>	<b>To Be Defined</b>
<b>V</b>	<b>Volt</b>
<b>W</b>	<b>Watt</b>
<b>WO</b>	<b>Work Order</b>
<b>WP</b>	<b>Work Package</b>
<b>Ω</b>	<b>Ohm</b>